



prolong

TIRE CONDITIONER

HEAVY-DUTY TRUCK HIGH SPEED APPLICATION

8 OZ. (240mL)

9-22.5

16 - 20 OZ. (475mL - 600mL)

10-22.5, 11-22.5, 11-24.5, 18-19.5,
12.5-22.5, 15-22.5

1 LITRE

18-22.5, 16.5-22.5

8 LITRES

12.00x24, 13.00x24-25, 14.00x24,
16.00x24, 20.00x24, 14.00x25,
15.5x25, 16.00x25, 17.5x25

12 LITRES

20.05x25, 21.00x25, 23.5x25,
25.65x25, 29.5x25, 18.00x25,
20x30.5, 21.00x49, 24.00x49

OFF THE ROAD LOW SPEED APPLICATION

16 LITRES

16.9x28, 29.5x29, 30.65x29,
33.25x29, 18.00x33, 33.5x33,
21.00x35, 20.00x39.5, 23x41.5,
18.9x49, 24.00x49, 27x56.5

20 LITRES

26.5x29, 35-65x33, 37.5x33,
24.00x35, 29.5x35, 33.25x35,
37.25x35, 27.00x41.4, 30x41.5,
33x41.5, 21.00x49, 27x49, 30x56.5

24 LITRES

37.5x39, 40-65x39, 40.5-75x39,
24.00x43, 45-65x45, 38x46.5,
40x46.5, 45x52.5

32 LITRES

30.00x51, 33.00x51, 36.00x51,
37.5x51, 50-65x51, 33x39.5, 36x59.5,
38x59.5, 39x59.5, 50x59.2

40 LITRES

40.00x57, 37.00x57, 44x66.5



(800) 272-4474 • info@mersinco.com

WILL NOT CORRODE MAGNESIUM OR ALUMINUM WHEELS.

VOLUMES SHOULD BE INCREASED BY 30% WHEN USED IN BIAS PLY TIRES.

SEVERE APPLICATIONS MAY REQUIRE AN ADDITIONAL 10% MORE THAN VOLUMES ABOVE.

DO NOT STORE IN OPEN CONTAINER. WARNING: DO NOT TAKE INTERNALLY. IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION. KEEP OUT OF REACH OF CHILDREN